

RECORD OF SURVEY 36-33

SEC. 19, T.2 S., R.28 E., M.D.B.&M.

COUNTY OF MONO

STATE OF CALIFORNIA

- (A) N.E. COR. SEC. 19: FOUND 4 IN. X 4 IN. POST IN CENTER OF 2 1/2 FT. DIA. STONE MOUND. SOME SCRIBING ON POST. REPLACED WITH A 2 3/8 IN. DIA. ALUMINUM PIPE 30 IN. LONG WITH A 3 1/4 IN. DIA. U.S. DEPT. OF AGRI. FOREST SERVICE CAP MARKED → RAISED A MOUND OF STONE 3 FT. DIA. AT BASE AROUND PIPE TO TOP. THE PIPE IS LOCATED ON A LEDGE ON THE SOUTH FACE OF ROCK OUTCROP. T2SR28E
S18|S17
S19|S20
LS4580
1983
- (B) N. 1/16 COR. BETWEEN SEC'S. 19 AND 20: SET A 2 3/8 IN. DIA. ALUMINUM PIPE 30 IN. LONG 26 IN. INTO GROUND WITH A 3 1/4 IN. DIA. U.S. DEPT. OF AGRI. FOREST SERVICE CAP MARKED → PLACED A SMALL ROCK MOUND AROUND PIPE. N 1/16
S19|S20
LS4580
1983
- (C) E. 1/4 COR. SEC. 19: NOT FOUND. SET A 2 3/8 IN. DIA. ALUMINUM PIPE 30 IN. LONG 24 IN. INTO GROUND WITH A 3 1/4 IN. DIA. U.S. DEPT. OF AGRI. FOREST SERVICE CAP MARKED → FROM WHICH, A 21 IN. DIA. PINE BEARS N. 36° 42' E., 104.0 FT. MARKED 1/4 S 20 BT. A 10 IN. DIA. PINE BEARS S. 82° 18' W., 79.9 FT. MARKED 1/4 S 19 BT. T2SR28E
S19|S20
LS4580
1983
- (D) S. 1/16 COR. BETWEEN SEC'S. 19 AND 20: SET A 2 3/8 IN. DIA. ALUMINUM PIPE 30 IN. LONG 26 IN. INTO GROUND WITH A 3 1/4 IN. DIA. U.S. DEPT. OF AGRI. FOREST SERVICE CAP MARKED → S 1/16
S19|S20
LS4580
1983
- (E) S. E. COR. SEC. 19: FOUND A 2 IN. DIA. I.P. UP 10 IN. IN FENCE LINE WITH AN ALUMINUM ROD AND CAP IN TOP OF PIPE MARKED → IN LIEU OF TAG PLACED ON 2 IN. IRON PIPE PER R.S. 36-29. 19|20
30|29
RCE21435
- (F) S. 1/4 COR. SEC. 19: NOT FOUND. SET A 2 3/8 IN. DIA. ALUMINUM PIPE 30 IN. LONG 24 IN. INTO GROUND WITH A 3 1/4 IN. DIA. U.S. DEPT. OF AGRI. FOREST SERVICE CAP MARKED → A 2 IN. X 2 IN. HUB WITH NAIL AND WASHER PER RECORD OF SURVEY FILED IN BOOK 2 PAGE 61 BEARS S. 71° 16' 50" E., 107.43 FT. NOT ACCEPTED AS 1/4 COR. T2SR28E
S19|S20
LS4580
1983
- (G) S. W. COR. SEC. 19: SET FROM BEARING TREES A 2 3/8 IN. DIA. ALUMINUM PIPE 30 IN. LONG 22 IN. INTO GROUND WITH A 3 1/4 IN. DIA. U.S. DEPT. OF AGRI. FOREST SERVICE CAP MARKED → FROM WHICH, A 52 IN. DIA. PINE STUMP BEARS S. 67° 49' E., 60.5 FT. G.L.O. RECORD IS A YELLOW PINE 36 IN. DIA. BEARS S. 67° E., 92 LINKS (60.7 FT.) A 46 IN. DIA. PINE SNAG BEARS N. 39° 50' E., 73.9 FT. G.L.O. RECORD IS A YELLOW PINE 40 IN. DIA. BEARS N. 40° E., 112 LINKS (73.9 FT.) A 42 IN. DIA. PINE BEARS N. 5° 10' W., 71.7 FT. G.L.O. RECORD IS A 24 IN. DIA. YELLOW PINE BEARS N. 5° W. 110 LINKS (72.6 FT.) THE CENTER OF A STUMP HOLE OF A DOWN AND ROTTED PINE BEARS S. 73° 26' W., 94.2 FT. G.L.O. RECORD IS A YELLOW PINE 30 IN. DIA. BEARS S. 73 1/2° W., 143 LINKS (94.4 FT.) A 9 IN. DIA. PINE BEARS N. 68° 28' E., 18.6 FT. MARKED T 2 S R 28 E S 19 BT. A 11 IN. DIA. PINE BEARS S. 78° 46' E., 21.8 FT. MARKED T 2 S R 28 E S 30 BT. A 14 IN. DIA. PINE BEARS S. 59° 57' W., 12.9 FT. MARKED T 2 S R 27 E S 25 BT. A 10 IN. DIA. PINE BEARS N. 23° 32' W., 24.7 FT. MARKED T 2 S R 27 E S 24 BT. T2SR28E
S24|S19
S25|S30
LS4580
1983
- (H) W. 1/4 COR. SEC. 19: NOT FOUND. SET A 2 3/8 IN. DIA. ALUMINUM PIPE 30 IN. LONG 24 IN. INTO GROUND WITH A 3 1/4 IN. DIA. U.S. DEPT. OF AGRI. FOREST SERVICE CAP MARKED → PLACED A SMALL ROCK MOUND AROUND PIPE. FROM WHICH, A 16 IN. DIA. PINE BEARS N. 40° 53' W., 49.5 FT. MARKED 1/4 S 24 BT. A 14 IN. DIA. PINE BEARS N. 73° 29' E., 26.3 FT. MARKED 1/4 S 19 BT. T2SR28E
S24|S19
LS4580
1983
- (I) N.W. COR. SEC. 19: SET FROM BEARING TREE A 2 3/8 IN. DIA. ALUMINUM PIPE 30 IN. LONG 26 IN. INTO GROUND WITH A 3 1/4 IN. DIA. U.S. DEPT. OF AGRI. FOREST SERVICE CAP MARKED → RAISED A MOUND OF STONE 3 FT. DIA. AT BASE AROUND PIPE TO TOP. FROM WHICH, A 44 IN. DIA. PINE BEARS N. 79° 15' E., 104.3 FT. ACCEPTED AS ORIGINAL B.T. G.L.O. RECORD IS A 36 IN. DIA. PINE. A 7 IN. DIA. PINE BEARS S. 48° 10' E., 10.2 FT. MARKED T 2 S R 28 E S 19 BT. A 10 IN. DIA. PINE BEARS S. 50° 41' W., 28.1 FT. MARKED T 2 S R 27 E S 24 BT. A 13 IN. DIA. PINE BEARS N. 46° 47' W., 41.9 FT. MARKED T 2 S R 27 E S 13 BT. T2SR28E
S13|S18
S24|S19
LS4580
1983
- (J) N. 1/4 COR. SEC. 19: SET FROM BEARING TREES A 2 3/8 IN. DIA. ALUMINUM PIPE 30 IN. LONG 26 IN. INTO GROUND WITH A 3 1/4 IN. DIA. U.S. DEPT. OF AGRI. FOREST SERVICE CAP MARKED → FROM WHICH, A 30 IN. DIA. PINE STUMP BEARS N. 78° 55' E., 60.1 FT. SOME SCRIBING VISIBLE IN OPENED BLAZE OF DOWN TREE. G.L.O. RECORD IS A PINE 18 IN. DIA. BEARS N. 79° E., 90 LINKS (59.4 FT.). A 30 IN. DIA. PINE BEARS S. 74° 36' E., 60.1 FT. G.L.O. RECORD IS A 24 IN. DIA. PINE BEARS S. 75° E., 92 LINKS (60.7 FT.). A 24 IN. DIA. PINE BEARS N. 36° 03' E., 47.1 FT. MARKED 1/4 S 19 BT. RAISED A MOUND OF STONE 2 1/2 FT. DIA. AT BASE AROUND PIPE TO TOP. T2SR28E
S18|S19
LS4580
1983
- (K) E. 1/16 COR. BETWEEN SEC'S. 18 AND 19: POINT FOR COR. FALLS IN ROAD. SET A 2 3/8 IN. DIA. ALUMINUM PIPE 30 IN. LONG 24 IN. INTO GROUND WITH A 3 1/4 IN. DIA. U.S. DEPT. OF AGRI. FOREST SERVICE CAP N. 82° 21' 52" E., 20.00 FT. ALONG SEC. LINE AT THE NORTH EDGE OF ROAD FOR A WITNESS COR. THE CAP IS MARKED → RAISED A MOUND OF STONE 2 1/2 FT. DIA. AT BASE AROUND PIPE TO TOP. WC
E 1/16
S18|S19
LS4580
1983
- (L) N.E. 1/16 COR. SEC. 19: SET A 2 3/8 IN. DIA. ALUMINUM PIPE 30 IN. LONG 26 IN. INTO GROUND WITH A 3 1/4 IN. DIA. U.S. DEPT. OF AGRI. FOREST SERVICE CAP MARKED → FROM WHICH, A 16 IN. DIA. PINE BEARS N. 28° 10' W., 20.9 FT. MARKED NE 1/16 S 19 BT. A 15 IN. DIA. PINE BEARS S. 73° 20' E., 59.0 FT. MARKED NE 1/16 S 19 BT. RAISED A MOUND OF STONE 2 1/2 FT. DIA. AT BASE AROUND PIPE TO TOP. NE 1/16
S19
LS4580
1983
- (M) E. 1/16 COR. SEC. 19: SET A 2 3/8 IN. DIA. ALUMINUM PIPE 30 IN. LONG 25 IN. INTO GROUND WITH A 3 1/4 IN. DIA. U.S. DEPT. OF AGRI. FOREST SERVICE CAP MARKED → FROM WHICH, A 13 IN. DIA. PINE BEARS N. 59° 59' W., 28.7 FT. MARKED C E 1/16 S 19 BT. A 15 IN. DIA. PINE BEARS N. 6° 51' E., 45.2 FT. MARKED C E 1/16 S 19 BT. A 2 IN. DIA. I.P. BEARS S. 4° 13' W., 99.25 FT. RAISED A MOUND OF STONE 2 1/2 FT. DIA. AT BASE AROUND PIPE TO TOP. E 1/16
C S19
LS4580
1983
- (N) S. E. 1/16 COR. SEC. 19: SET A 2 3/8 IN. DIA. ALUMINUM PIPE 30 IN. LONG 28 IN. INTO GROUND WITH A 3 1/4 IN. DIA. U.S. DEPT. OF AGRI. FOREST SERVICE CAP MARKED → PLACED A MOUND OF STONE 28 IN. DIA. AROUND PIPE. SE 1/16
S19
LS4580
1983
- (O) S. 1/16 COR. SEC. 19: SET A 2 3/8 IN. DIA. ALUMINUM PIPE 30 IN. LONG 29 IN. INTO GROUND WITH A 3 1/4 IN. DIA. U.S. DEPT. OF AGRI. FOREST SERVICE CAP MARKED → C
S 1/16
S19
LS4580
1983
- (P) S. W. 1/16 COR. SEC. 19: SET A 2 3/8 IN. DIA. ALUMINUM PIPE 30 IN. LONG 22 IN. INTO GROUND WITH A 3 1/4 IN. DIA. U.S. DEPT. OF AGRI. FOREST SERVICE CAP MARKED → FROM WHICH, A 14 IN. DIA. PINE BEARS S. 61° 37' W., 97.3 FT. MARKED S W 1/16 S 19 BT. A 16 IN. DIA. PINE BEARS N. 50° 07' W., 32.1 FT. MARKED S W 1/16 S 19 BT. SW 1/16
S19
LS4580
1983
- (Q) W. 1/16 COR. SEC. 19: SET A 2 3/8 IN. DIA. ALUMINUM PIPE 30 IN. LONG 24 IN. INTO GROUND WITH A 3 1/4 IN. DIA. U.S. DEPT. OF AGRI. FOREST SERVICE CAP MARKED → FROM WHICH, A 20 IN. DIA. PINE BEARS N. 31° 08' W., 55.4 FT. MARKED C W 1/16 S 19 BT. A 14 IN. DIA. PINE BEARS N. 50° 58' E., 63.9 FT. MARKED C W 1/16 S 19 BT. W 1/16
C S19
LS4580
1983
- (R) C. 1/4 COR. SEC. 19: SET A 2 3/8 IN. DIA. ALUMINUM PIPE 30 IN. LONG 24 IN. INTO GROUND WITH A 3 1/4 IN. DIA. U.S. DEPT. OF AGRI. FOREST SERVICE CAP MARKED → FROM WHICH, A 14 IN. DIA. PINE BEARS N. 52° 12' E., 54.9 FT. MARKED C 1/4 S 19 BT. A 18 IN. DIA. PINE BEARS N. 51° 50' W., 41.9 FT. MARKED C 1/4 S 19 BT. T2SR28E
C 1/4
S19
LS4580
1983