

RECORD OF SURVEY NO. 34-28

IN THE UNINCORPORATED TERRITORY OF THE COUNTY OF MONO, STATE OF CALIFORNIA
BEING PORTIONS OF SECTIONS 4,5,8 AND 9, TOWNSHIP 1 NORTH, RANGE 26 EAST M. D. B. & M.

MONUMENT SCHEDULE

MONUMENT MARKED		MONUMENT NOTES		MONUMENT MARKED		MONUMENT NOTES	
		NOTE: ALL MONUMENTS SET HAVE 3/4" ALUMINUM CAPS MARKED U.S. DEPT. OF AGRICULTURE FOREST SERVICE		⑬	T I N R 2 6 E 1 4 S 9 S 10 L S 4 5 8 0 1 9 8 8	FD. A STONE 16"x11"x4" LYING ON ITS SIDE 4" BELOW THE SURFACE WITH 1/4 CHISELED ON IT'S FACE. PER MB 6/51 RESET WITH AN 18"x2 1/2" DIAM. ALUM. PIPE, FLUSH. DEPOSITED STONE ALONGSIDE PIPE.	
①	T I N R 2 6 E 1 4 S 5 S 4 L S 4 5 8 0 1 9 8 8	FD. 2 3" S.C.E BRASS CAPS SET 0.1' DOWN MKD. RCE 7211 S.C.E. CO. R.P. 5 FT. PER RS 5/118-123 SET 30"x2 1/2" DIAM. ALUM. PIPE, FLUSH		⑭	R C E 3 0 0 2 9	FD. 1/2" REBAR WITH TAG MARKED RCE 30029, UP 0.3'. PER RS 34-30 RSMB 1/102.	
②	C 1 S 4 4 W C L S 4 5 8 0 1 9 8 8	POINT FOR TRUE POSITION FALLS IN ROADWAY SET W.C. ON THE N-S CENTERLINE OF SEC. 4 N 0°10'06" E 14.68' FROM TRUE POSITION. SET 18"x2 1/2" DIAM. ALUMIN. PIPE, UP 0.1' RAISED A STONE MOUND 2' DIAM. x 6" HIGH AROUND POST.		⑮	L S 4 5 8 7	FD. A 2" I.P. WITH TAG MARKED LS 4587 IN A MOUND OF STONES. PER RS 34-30 RSMB 1/102.	
③	T I N R 2 6 E 1 4 S 4 S 3 L S 4 5 8 0 1 9 8 8	FD. ROCK MOUND 3 1/2' DIAM. x 1' HIGH WITH 4"x4" DEPRESSION IN CENTER, ACCEPTED AS ORIGINAL 1/4 CORNER. RESET WITH A 30"x2 1/2" DIAM. ALUM. PIPE, RAISED A MOUND OF STONE 3' DIAM. x 8" HIGH AROUND POST.		⑯	L E E V I N I N G 1 9 5 6	FD. A 3" BRASS DISC UP 0.2' AND LOCATED APPROX. 50' NE OF HWY. 395, N. OF A LARGE PROPANE TANK. DISC IS STAMPED "LEE VINING 1956"	
④	R C E 7 2 1 1	FD. A 4"x4" REDWOOD POST, FIRMLY SET, UP 2.8' WITH TAG RCE 7211 SET IN CENTER OF TOP. FD. 3" S.C.E. BRASS CAPS MARKED: RCE 7211 R.P., 5' EAST & 5' WEST OF CORNER. PER RS 5/118-123. ACCEPTED AS 1/4 CORNER S 5 S 8		⑰	R / W S 5 S 8 L S 4 5 8 0 1 9 8 8	FD. 2x2 HUB AND TACK WITH LATH MARKED 62+53.14 150' RT. PER CAL TRANS R/W SHEET 9 MNO 395 PM 52.2. RESET WITH A 18"x2 1/2" ALUM. PIPE, SET FLUSH.	
⑤	T I N R 2 6 E E 1 S 5 16 S 8 L S 4 5 8 0 1 9 8 8	SET A 30"x2 1/2" DIAM. ALUM. PIPE, UP 2" RAISED A MOUND OF STONES 2' DIAM. x 3" HIGH AROUND POST.		⑱		FD. 2x2 HUB AND TACK WITH LATH MARKED 60+00 150' RT. PER CAL TRANS R/W SHEET 9 MNO 395 PM 52.2.	
⑥	T I N R 2 6 E S 5 S 4 S 8 S 9 L S 4 5 8 0 1 9 8 8	FD. A ROCK MOUND 3' DIAM. x 1' HIGH WITH 2x2 & TACK IN CENTER. FD. 3" S.C.E. BRASS CAPS MARKED "RCE 7211 S.C.E. CO. 5 FT. R.P." 5' NORTH & WEST OF ROCK MOUND. PER RS 5/118-123. RESET WITH A 18"x2 1/2" DIAM. ALUM. PIPE, SET FLUSH IN CENTER OF FD. ROCK MOUND.		⑲		FD. 2x2 HUB AND TACK WITH LATH MARKED 60+00 100' RT. PER CAL TRANS R/W SHEET 9 MNO 395 PM 52.2.	
⑦	W 1 S 4 16 S 9 L S 4 5 8 0 1 9 8 8	FD. CAPPED 1" I.P. UP 14", LEANING 0.5' WEST, APPEARS TO HAVE SLID DOWNHILL. PER MB 6/51. RESET WITH A 30"x2 1/2" DIAM. ALUM. PIPE, UP 10".		⑳		FD. 2x2 HUB AND TACK, SET FLUSH. ACCEPTED AS 42+65.82 100' RT. PER CAL TRANS R/W SHEET 9 MNO 395 PM 51.6	
⑧	T I N R 2 6 E 1 S 4 4 S 9 L S 4 5 8 0 1 9 8 8	FD. A ROCK MOUND 3 1/2' BASE x 1 1/2' HIGH WITH A CHARRED CEDAR POST LYING ALONGSIDE. PER MB 6/51, RS 5/118-123 RESET WITH A 18"x2 1/2" DIAM. ALUM. PIPE, UP 3". RAISED A MOUND OF STONE 4' BASE x 1' HIGH AROUND PIPE.		㉑	P R O P . C O R . N O . 1 R / W 4 1 3 5 . 3 0 L S 4 5 8 0 1 9 8 8	FD. 2x2 HUB AND TACK WITH LATH MARKED 41+35.30 ANGLE PT. 100' RT. PER CAL TRANS R/W SHEET 9 MNO 395 PM 51.6. ACCEPTED AS SCHOOL PROPERTY CORNER. RESET WITH A 30"x2 1/2" DIAM. ALUM. PIPE, UP 4".	
⑨	T I N R 2 6 E S 4 S 3 S 9 S 10 L S 4 5 8 0 1 9 8 8	FD. ROCK MOUND, 2' BASE x 0.5' HIGH. FD. 4x4 REDWOOD POST SET 1.3' WEST OF MOUND. ACCEPTED MOUND AS CORNER. RESET WITH A 30"x2 1/2" DIAM. ALUM. PIPE, UP 0.4' IN ORIGINAL ROCK MOUND.		㉒	P R O P . C O R . N O . 2 L S 4 5 8 0 1 9 8 8	SET AT RIGHT ANGLES TO E'LY R/W LINE OF HWY. 395 PER MB 6/51 & CAL TRANS R/W SHEET 9 MNO 395 PM 51.6. SET A 30"x2 1/2" DIAM. ALUM. PIPE, UP 3".	
⑩		FD. A 1" I.P. WITH THREADED CAP, UP 0.2' PER MB 6/51 & CAL TRANS R/W MAP 9 MNO 395 PM 51.6. ACCEPTED AS 1/4 CORNER.		㉓	P R O P . C O R . N O . 3 L S 4 5 8 0 1 9 8 8	SET A 30"x2 1/2" DIAM. ALUM. PIPE, UP 6" AT RECORD BEARING DIFFERENCE PER MB 6/51, AND AT INTERSECTION WITH THE NORTH LINE OF THE SW 1/4 OF THE NW 1/4 OF SECTION 9. RAISED A MOUND OF STONES, 2' BASE AROUND POST TO TOP.	
⑪		FD. CAPPED 1" I.P. UP 0.2'. PER MB 6/51, CAL TRANS R/W MAP 9 MNO 395 PM 51.6. ACCEPTED AS C-W 1/16		㉔		SEARCHED FOR, NOT FOUND. POINT APPEARS TO FALL UNDER HWY. FILL MATERIAL. POINT = U.S. HWY. 395 STA. 41 35.30, 50' RT	
⑫	X	FD. CHISELED "X" ON A 14"x12"x6" HIGH ROCK PER MB 6/51. ACCEPTED AS CENTER 1/4 CORNER.		㉕		SEARCHED FOR, NOT FOUND. POINT APPEARS TO FALL UNDER HWY. FILL MATERIAL. POINT = U.S. HWY. 395 STA. 29 85.30, 50' RT.	

Vol. 2 Page 46B